


High pressure cleaner

Cold water, mobile, petrol operated - series KDB

KDB940




**3400
U/min**



Type		KDB940-Standard
Engine	Gasoline	<ul style="list-style-type: none"> ▶ 10m HP-Hose DN08 - 315bar ▶ Trigger-Gun with swivel ▶ Spray-Lance 900mm c/w Vario- Nozzle ▶ Stainless-Steel Jet-Nozzle 25° ▶ Detergent-Supply c/w Low-Pressure Injector and metering-valve
Operating pressure	30-150bar/ 3-15MPa	
Max. pressure	170bar/ 17MPa	
Discharge capacity	300 - 750l/h	
Nozzle size	043	
Max. Inlet temperature	45°C	
Pump speed	3400rpm	
Connected load	5,5h.p. Honda	
Electric-Starter	n/a.	
Weight net / with package		39,1 kg / 34,7 kg
Dimensions device / with package (LxWxH)		520x690x550 mm/ 771x458x926 mm
<p>Robust, corrosion-resistant, self-supporting device chassis made of robust steel pipe galvanized and powder-coated, trip-lex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, 2-fold safety system, unloader safety-valve c/w Infinitely variable pressure and quantity regulation and safety-valve, 2, large rubber-pneumatic tires for rough terrain with rubber stand, external detergent supply</p>		
Art. No.		101940

EHRLE attributes

High pressure cleaner characteristics



Triplex-Piston-Pump

Ceramic pump plunger, Stainless Steel pump valves and brass pump-head for long durability.

1400 U/min

All EHRLE High-Pressure Cleaners are equipped with slow-running, air-cooled and 4-pole electric Motors.



TSS-System with pump off delay

During breaks longer than 90 seconds, the unit switches automatically to stand-by position. After opening the trigger-gun again, the unit is immediately ready for operation. **The durability of the High-Pressure Pump is also higher.**

TOTAL STOP

Total Switch off after 20min

In case the Unit is not used in the stand-by mode for more than 20min it will switch off itself. The Unit can be re-started at the On/Off Switch for normal operation.



High-Pressure Chemical with Dosing-Valve

Any cleaning-detergents can be applied during high-pressure stage by opening the Dosing-Valve. The High-Pressure Pump will absorb detergents together with water and pressurize it.



Leakage Recognition

In the event of leaking parts in the High-Pressure Cleaner, or any Gun or Hose leaking, the Unit shuts itself down.



Information on recommended daily time of use.



Optical Flame-Monitor

on all High-Pressure Cleaners of Series ETRONIC II and static Units in order to comply with legal requirements.



Water-Break Tank for Separation

No additional check unit Valve necessary – Machines conforms to Water-Board Regulations. 30% increased Cleaning-Power due to no Chemical-Injector. Water-Break Tank help to protects pump from water starvation.



The quick-coupling system

by using the EHRLE QC315 quick-coupling system Accessories, Guns, Lances and Nozzles can be changed without the use of Tools. The EHRLE QC315 Guns incorporate an anti-twist Swivel for Hoses.



Patent Wheel-Brake

(requirement by Law) with large rubber-wheels – no small castors.



(Option) Water-Break Tank



(Optional)

This professional **Hose-Reel** with stainless steel shaft is equipped with a folding handle doubling as a reel-brake. Up to 40m of High-Pressure Hose on the hose-reel ensure a wide action radius and easy storage.

EHRLE horizontal-heatcoil

with 3-pass System. Highest Efficiency – with environmentally friendly low Emmissions! No additional insulation required – cold air is used to cool the Boiler. Separate Burner-Motor for professional use, ensures increased reliability.

